

Description

Shear application, high temperature alloy, silver plated, Hi-Lok, HL97 series collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HL975
Minimum Qty (MOQ):	2
NSN:	5320-01-005-4086
Schedule B:	7326.90.8688
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N HL97-5 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.283 Inches Minimum And 0.287 Inches Maximum
Collar Overall Height:	0.427 Inches Minimum And 0.447 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.166 Inches Minimum And 0.173 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Collar Style:	Threaded (break Off) Type
Material:	Iron Alloy 660 Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HL97-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.