

P/N HLT170-10

Description

Thread Size: 1/4

Order this part online

Additional Information

SKU / Model: HLT17010
Minimum Qty (MOQ): 1

NSN: 5320-00-039-0097

Schedule B: 7616.10.1000

ECCN: EAR99

National Motor Freight: 013630, Alum Rivets



^{*} Manufacturer certifications are shipped with your order EREE of charge

^{*} See page 2 for technical characteristics

P/N HLT170-10 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Green
Collar Outside Diameter:	0.550 Inches Minimum And 0.555 Inches Maximum
Collar Overall Height:	0.735 Inches Minimum And 0.755 Inches Maximum
Lubrication:	Cetyl Alcohol
Collar Inside Diameter:	0.324 Inches Minimum And 0.330 Inches Maximum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.312 Inches
Collar Style:	Threaded (break Off) Type
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall Or Qq-a-225/6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this collar from our inventory online by visiting https://military-fasteners.com/collars/collars/HLT170-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/collars/collars/HLT170-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/collars/collars/HLT170-10 and selecting the quantity you want then click "add to cart".