

Description

Thread Size: 1/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | HLT1705 |
| Minimum Qty (MOQ): | 15 |
| NSN: | 5320-01-516-2991 |
| Schedule B: | 7616.10.1000 |
| ECCN: | 9A991 |



P/N HLT170-5 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Collar Outside Diameter: | 0.307 Inches Minimum And 0.312 Inches Maximum |
| Collar Overall Height: | 0.475 Inches Nominal |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Collar Inside Diameter: | 0.125 Inches Minimum |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.164 Inches |
| Collar Style: | Threaded (break Off) Type |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall Or Qq-a-225/6 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HLT170-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.