

Description

Thread Size: 1/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HLT1705
Minimum Qty (MOQ):	15
NSN:	5320-01-516-2991
Schedule B:	7616.10.1000
ECCN:	9A991



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HLT170-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Collar Outside Diameter:	0.307 Inches Minimum And 0.312 Inches Maximum
Collar Overall Height:	0.475 Inches Nominal
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.125 Inches Minimum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Collar Style:	Threaded (break Off) Type
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall Or Qq-a-225/6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HLT170-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.