

Description

Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HLT1708
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-039-0109
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N HLT170-8 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Green
Collar Outside Diameter:	0.425 Inches Minimum And 0.430 Inches Maximum
Collar Overall Height:	0.605 Inches Minimum And 0.625 Inches Maximum
Lubrication:	Cetyl Alcohol
Collar Inside Diameter:	0.261 Inches Minimum And 0.265 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Special Features:	Color Green
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall Or Qq-a-225/6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this hlt collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HLT170-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.