

Description

Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------|
| SKU / Model: | HLT1708 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-00-039-0109 |
| Schedule B: | 7616.10.9090 |
| ECCN: | 9A991 |
| National Motor Freight: | 013630, Alum Rivets |

NO IMAGE
AVAILABLE

P/N HLT170-8 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Identification Code Color: | Green |
| Collar Outside Diameter: | 0.425 Inches Minimum And 0.430 Inches Maximum |
| Collar Overall Height: | 0.605 Inches Minimum And 0.625 Inches Maximum |
| Lubrication: | Cetyl Alcohol |
| Collar Inside Diameter: | 0.261 Inches Minimum And 0.265 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Special Features: | Color Green |
| Heat Treatment: | T-6 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall Or Qq-a-225/6 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this hlt collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HLT170-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.