

Description

Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HLT1718AW
Minimum Qty (MOQ):	1 EA
NSN:	5320-00-036-7068
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N HLT171-8AW Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Green
Collar Outside Diameter:	0.465 Inches Minimum And 0.475 Inches Maximum
Collar Overall Height:	0.605 Inches Minimum And 0.625 Inches Maximum
Lubrication:	Cetyl Alcohol
Collar Inside Diameter:	0.270 Inches Nominal
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Heat Treatment:	T-6 Solution Heat Treated Collar
Material:	Aluminum Alloy 2024 Collar
Material:	Steel Comp 630 Washer Or Steel Comp 631 Washer
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Washer Or Ams5528 Assn Std 2nd Material Response Washer
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Collar Or Qq-4-225/6 Fed Spec Single Material Response Collar
Surface Treatment:	Cadmium Washer And Chromate Washer
Surface Treatment:	Anodize Collar
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Collar
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Washer
Thread Series Designator:	Unjf

How to Order

Order this hlt washer from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HLT171-8AW and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.