

Description

Thread Size: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HLT286PB16
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-514-9663
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N HLT286PB16 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.870 Inches Minimum And 0.880 Inches Maximum
Collar Overall Height:	0.822 Inches Minimum And 0.942 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.537 Inches Minimum And 0.543 Inches Maximum
End Item Identification:	A-10
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	25000 Pounds Per Square Inch
Nominal Thread Size:	0.500 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 303 Overall
Material Document And Classification:	Astm A 582 Assn Std Single Material Response Overall Or Ams 5640 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type II,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this hl pin from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HLT286PB16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.