

**Description**

Thread Size: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HLT286PB16
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-514-9663
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N HLT286PB16 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.870 Inches Minimum And 0.880 Inches Maximum
<b>Collar Overall Height:</b>	0.822 Inches Minimum And 0.942 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Collar Inside Diameter:</b>	0.537 Inches Minimum And 0.543 Inches Maximum
<b>End Item Identification:</b>	A-10
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	25000 Pounds Per Square Inch
<b>Nominal Thread Size:</b>	0.500 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Material:</b>	Steel Comp 303 Overall
<b>Material Document And Classification:</b>	Astm A 582 Assn Std Single Material Response Overall Or Ams 5640 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type li,class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this hl pin from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HLT286PB16](https://military-fasteners.com/collars/pin_rivet+collars/HLT286PB16) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.