

Description

Thread Size: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[HLT-73-6](#)

SKU / Model:	HLT736
Minimum Qty (MOQ):	2
NSN:	5320-00-500-5621
Schedule B:	7319.90.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HLT73-6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.303 Inches Minimum And 0.307 Inches Maximum
Collar Overall Height:	0.427 Inches Minimum And 0.447 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.201 Inches Minimum And 0.205 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 630 Overall
Material Document And Classification:	Ams 5643 Assn Std Single Material Response Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-riev collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HLT73-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.