

## **P/N HLT73-8**

### **Description**

Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

 SKU / Model:
 HLT738

 Minimum Qty (MOQ):
 1 EA

 NSN:
 5320-00-500-5624

Schedule B: 7318.24.0000

ECCN: 9A991

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# **P/N HLT73-8 Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.407 Inches Minimum And 0.413 Inches Maximum
Collar Overall Height:	0.512 Inches Minimum And 0.532 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.261 Inches Minimum And 0.265 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 630 Overall
Material Document And Classification:	Ams 5643 Assn Std Single Material Response Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this hlt collar from our inventory online by visiting <a href="https://military-fasteners.com/collars/pin\_rivet+collars/HLT73-8">https://military-fasteners.com/collars/pin\_rivet+collars/HLT73-8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.