

Description

shear application - 2024-t6 aluminum alloy - anodized

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HLT778
Minimum Qty (MOQ):	10
NSN:	5320-01-183-3435
National Motor Freight:	013630, Alum Rivets



* See page 2 for technical characteristics

P/N HLT77-8 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.408 Inches Minimum And 0.412 Inches Maximum
Collar Overall Height:	0.530 Inches Minimum And 0.550 Inches Maximum
Collar Inside Diameter:	0.261 Inches Minimum And 0.265 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Collar Style:	Threaded (break Off) Type
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall Or Qq-a-225/6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HLT77-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.