

Description

Ring part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HS3014RR50
Minimum Qty (MOQ):	65 EA
NSN:	5325-01-178-5008
Schedule B:	7318.29.0000
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HS3014RR50 Specifications

Cross-sectional Shape Style:	Double Oval
Inside Diameter:	0.442 Inches Nominal
Casehardening Indicator:	Not Casehardened
Outside Diameter:	0.532 Inches Minimum And 0.545 Inches Maximum
Major Thickness:	0.023 Inches Minimum And 0.027 Inches Maximum
Ring Style:	Spiral
Usage Design:	Internal
Strength Rating:	221000.0 Pounds Per Square Inch Minimum Tensile
Material:	Steel, Sae 1070 Or Steel, Sae 1072 Or Steel, Sae 1074 Or Steel, Sae 1075 Or Steel, Sae 1078 Or Steel, Sae 1080 Or Steel, Sae 1084 Or Steel, Sae 1085 Or Steel, Sae 1086 Or Steel, Sae 1090 Or Steel, Aisi 1070 Or Steel, Aisi 1074 Or Steel, Aisi 1078 Or Steel, Aisi 1080 Or Steel, Aisi 1084 Or Steel, Aisi 1085 Or Steel, Aisi 1090 Or Steel, Fed Std 66, Comp 1070 Or Steel, Fed Std 66, Comp 1072 Or Steel, Fed Std 66, Comp 1074 Or Steel, Fed Std 66, Comp 1075 Or Steel, Fed Std 66, Comp 1078 Or Steel, Fed Std 66, Comp 1080 Or Steel, Fed Std 66, Comp 1084 Or Steel, Fed Std 66, Comp 1085 Or Steel, Fed Std 66, Comp 1086 Or Steel, Fed Std 66, Comp 1090 Or Steel, Mil-s-46049
Material:	Steel Comp 1065 Or Steel Comp 1075 Or Steel Comp 1085 Or Steel Comp 1095

How to Order

Order this ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/HS3014RR50> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.