

Description

Fastener Length: 3-7/16", Thread: 3/4-16, Thread Length: 1-5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HS4243V12H34
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-457-3397
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N HS4243V12H34 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.314 Inches Nominal
Fastener Length:	3.439 Inches Nominal
Head Style:	Double Hexagon Extended Washer
Head Height:	0.711 Inches Nominal
Width Between Flats:	0.803 Inches Minimum And 0.814 Inches Maximum
Extended Washer Diameter:	1.220 Inches Minimum And 1.230 Inches Maximum
Extended Washer Thickness:	0.178 Inches Nominal
Grip Diameter:	0.748 Inches Minimum And 0.749 Inches Maximum
Nominal Thread Diameter:	0.750 Inches
Grip Length:	2.125 Inches Minimum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	260000 Pounds Per Square Inch
Material:	Cobalt Comp Mp-35-n Overall
Material Document And Classification:	Ams5758 Assn Std 1st Material Response Overall Or Ams5844 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Mil-c-8867 Ty 2 Or Ty 3 Cl 2 Mil Spec 1st Treatment Response Overall Or Mil-c-46010 Ty 1 Mil Spec 2nd Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/HS4243V12H34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.