



Military-Fasteners.com

P/N HS4243V12H34

Description

Fastener Length: 3-7/16", Thread: 3/4-16, Thread Length: 1-5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HS4243V12H34
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-457-3397
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N HS4243V12H34 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.314 Inches Nominal
<b>Fastener Length:</b>	3.439 Inches Nominal
<b>Head Style:</b>	Double Hexagon Extended Washer
<b>Head Height:</b>	0.711 Inches Nominal
<b>Width Between Flats:</b>	0.803 Inches Minimum And 0.814 Inches Maximum
<b>Extended Washer Diameter:</b>	1.220 Inches Minimum And 1.230 Inches Maximum
<b>Extended Washer Thickness:</b>	0.178 Inches Nominal
<b>Grip Diameter:</b>	0.748 Inches Minimum And 0.749 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.750 Inches
<b>Grip Length:</b>	2.125 Inches Minimum
<b>Thread Quantity Per Inch:</b>	16
<b>Minimum Tensile Strength:</b>	260000 Pounds Per Square Inch
<b>Material:</b>	Cobalt Comp Mp-35-n Overall
<b>Material Document And Classification:</b>	Ams5758 Assn Std 1st Material Response Overall Or Ams5844 Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-8867 Ty 2 Or Ty 3 Cl 2 Mil Spec 1st Treatment Response Overall Or Mil-c-46010 Ty 1 Mil Spec 2nd Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/HS4243V12H34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.