

**Description**

Fastener Length: 3/4", Thread: 3/8-24, Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | HS52870601                                |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-01-177-5714                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N HS5287-06-01 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.751 Inches Nominal  |
| <b>Fastener Length:</b>                               | 0.810 Inches Nominal  |
| <b>Head Style:</b>                                    | Spline Extended Washer  |
| <b>Head Height:</b>                                   | 0.388 Inches Nominal  |
| <b>Extended Washer Diameter:</b>                      | 0.639 Inches Minimum And 0.649 Inches Maximum                       |
| <b>Extended Washer Thickness:</b>                     | 0.091 Inches Nominal  |
| <b>Head Minor Diameter:</b>                           | 0.437 Inches Nominal  |
| <b>Nominal Thread Diameter:</b>                       | 0.375 Inches  |
| <b>Hole Quantity:</b>                                 | 4   |
| <b>Hole Type:</b>                                     | Drilled   |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| <b>Hole Configuration Style:</b>                      | Double Hexagon Longitudinal Hole                                    |
| <b>Special Features:</b>                              | Dry Film Lub,mil-I-46010,ty 1                                       |
| <b>Material:</b>                                      | Steel Overall   |
| <b>Material Document And Classification:</b>          | Mil-s-6049 Mil Spec Single Material Response Overall                |
| <b>Surface Treatment:</b>                             | Nickel Overall  |
| <b>Special Test Features:</b>                         | Embrittlement Relief,bake 23 Hrs, 375 +/- 25 Deg                    |
| <b>Surface Treatment Document And Classification:</b> | Qq-n-290,ty 1 Fed Spec Single Treatment Response Overall            |
| <b>Thread Series Designator:</b>                      | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/HS5287-06-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.