



Military-Fasteners.com

P/N HS5287-06-01

Description

Fastener Length: 3/4", Thread: 3/8-24, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HS52870601
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-177-5714
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N HS5287-06-01 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.751 Inches Nominal
Fastener Length:	0.810 Inches Nominal
Head Style:	Spline Extended Washer
Head Height:	0.388 Inches Nominal
Extended Washer Diameter:	0.639 Inches Minimum And 0.649 Inches Maximum
Extended Washer Thickness:	0.091 Inches Nominal
Head Minor Diameter:	0.437 Inches Nominal
Nominal Thread Diameter:	0.375 Inches
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Special Features:	Dry Film Lub,mil-I-46010,ty 1
Material:	Steel Overall
Material Document And Classification:	Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Nickel Overall
Special Test Features:	Embrittlement Relief,bake 23 Hrs, 375 +/- 25 Deg
Surface Treatment Document And Classification:	Qq-n-290,ty 1 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/HS5287-06-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.