

**Description**

Fastener Length: 3/4", Thread: 3/8-24, Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HS52870601
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-177-5714
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N HS5287-06-01 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.751 Inches Nominal
<b>Fastener Length:</b>	0.810 Inches Nominal
<b>Head Style:</b>	Spline Extended Washer
<b>Head Height:</b>	0.388 Inches Nominal
<b>Extended Washer Diameter:</b>	0.639 Inches Minimum And 0.649 Inches Maximum
<b>Extended Washer Thickness:</b>	0.091 Inches Nominal
<b>Head Minor Diameter:</b>	0.437 Inches Nominal
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Hole Quantity:</b>	4
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Hole Configuration Style:</b>	Double Hexagon Longitudinal Hole
<b>Special Features:</b>	Dry Film Lub,mil-I-46010,ty 1
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Mil-s-6049 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Nickel Overall
<b>Special Test Features:</b>	Embrittlement Relief,bake 23 Hrs, 375 +/- 25 Deg
<b>Surface Treatment Document And Classification:</b>	Qq-n-290,ty 1 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/HS5287-06-01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.