

Description

Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HS55806
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-225-0506
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HS5580-6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.355 Inches Minimum And 0.365 Inches Maximum
Collar Overall Height:	0.432 Inches Minimum And 0.452 Inches Maximum
Lubrication:	Grease Film
Collar Inside Diameter:	0.255 Inches Nominal
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 303se Overall
Material Document And Classification:	Qq-s-764 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 1,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HS5580-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.