



Military-Fasteners.com

P/N HS5583-5

Description

Thread Size: 5/32

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HS55835
Minimum Qty (MOQ):	25
NSN:	5320-00-841-8007
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N HS5583-5 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	0.283 Inches Minimum And 0.287 Inches Maximum
<b>Collar Overall Height:</b>	0.427 Inches Minimum And 0.447 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Collar Inside Diameter:</b>	0.166 Inches Minimum And 0.173 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Material:</b>	Steel Comp 303se Overall
<b>Material Document And Classification:</b>	Qq-s-764 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 1,class 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this pin-rivet collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HS5583-5](https://military-fasteners.com/collars/pin_rivet+collars/HS5583-5) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.