

Description

Thread Size: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HS56136
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-471-2815
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

P/N HS5613-6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Identification Code Color:	Brown
Collar Outside Diameter:	0.355 Inches Minimum And 0.365 Inches Maximum
Collar Overall Height:	0.445 Inches Nominal
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.210 Inches Nominal
End Item Identification:	1520013558250
Features Provided:	Washer
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.188 Inches
Collar Style:	Threaded (break Off) Type
Material:	Aluminum Alloy 2024 Body
Material:	Steel Comp 630 Washer Or Steel Comp 631 Washer Or Steel Comp 632 Washer
Material Document And Classification:	Ams5643 Assn Std Single Material Response Washer Or Ams5528 Assn Std Single Material Response Washer Or Ams5520 Assn Std Single Material Response Washer
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Collar Or Qq-a-225/6 Fed Spec Single Material Response Collar
Surface Treatment:	Cadmium Washer
Surface Treatment:	Anodize Collar
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Body
Surface Treatment Document And Classification:	Qq-p-416,type 1, Class 2 Fed Spec Single Treatment Response Washer
Thread Series Designator:	Unjc

How to Order

Order this collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HS5613-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.