



★ FASTENERS

Military-Fasteners.com

P/N HST10AG6-5

Description

Diameter: 3/16", Grip Length: 5/16", thread: 10-32, protruding shear head, titanium, aluminum coating

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HST10AG65
Minimum Qty (MOQ):	10
NSN:	5320-01-338-4247
Schedule B:	8108.90.8000
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N HST10AG6-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.592 Inches Minimum And 0.612 Inches Maximum
Head Style:	Err-090
Head Height:	0.045 Inches Minimum And 0.055 Inches Maximum
Width Between Flats:	0.0791 Inches Minimum And 0.0806 Inches Maximum
Shank Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.295 Inches Minimum And 0.315 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.307 Inches Minimum And 0.317 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Special Features:	Color Code Orange On Thread End
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Hi Kote 1,cagec 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HST10AG6-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.