

**Description**

HST10AG8-7 Pin-Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HST10AG87
Minimum Qty (MOQ):	5
NSN:	5320-01-338-3184
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets



NO IMAGE  
AVAILABLE

## P/N HST10AG8-7 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.748 Inches Minimum And 0.768 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.059 Inches Minimum And 0.069 Inches Maximum
<b>Width Between Flats:</b>	0.0947 Inches Minimum And 0.0967 Inches Maximum
<b>Shank Diameter:</b>	0.2485 Inches Minimum And 0.2495 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Straight, Threaded
<b>Head Major Diameter:</b>	0.387 Inches Minimum And 0.412 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Grip Length:</b>	0.433 Inches Minimum And 0.443 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Shear Strength:</b>	95000 Single Pounds Per Square Inch
<b>Special Features:</b>	Color Code Orange On Thread End
<b>Material:</b>	Titanium Alloy Uns R56400 Overall
<b>Material Document And Classification:</b>	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Aluminum Overall
<b>Surface Treatment Document And Classification:</b>	Hi Kote 1,cagec 73197 Mfr Ref Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HST10AG8-7](https://military-fasteners.com/pins/pin_rivets/HST10AG8-7) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.