

**Description**

HST10AG8-8 Pin-Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | HST10AG88                                 |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5320-01-338-3185                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



NO IMAGE  
AVAILABLE

## P/N HST10AG8-8 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Fastener Length:</b>                               | 0.810 Inches Minimum And 0.830 Inches Maximum  |
| <b>Head Style:</b>                                    | Err-090  |
| <b>Head Height:</b>                                   | 0.059 Inches Minimum And 0.069 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.0947 Inches Minimum And 0.0967 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.2485 Inches Minimum And 0.2495 Inches Maximum  |
| <b>Head Major Diameter:</b>                           | 0.387 Inches Minimum And 0.412 Inches Maximum  |
| <b>Lubrication:</b>                                   | Cetyl Alcohol, Spec 305, Hi-shear Corp   |
| <b>Grip Length:</b>                                   | 0.495 Inches Minimum And 0.505 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 28   |
| <b>Nominal Thread Size:</b>                           | 0.250 Inches   |
| <b>Shear Strength:</b>                                | 95000 Single Pounds Per Square Inch  |
| <b>Special Features:</b>                              | Color Code Orange On Thread End  |
| <b>Material:</b>                                      | Titanium Alloy Uns R56400 Overall  |
| <b>Material Document And Classification:</b>          | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Aluminum Overall   |
| <b>Surface Treatment Document And Classification:</b> | Hi Kote 1,cagec 73197 Mfr Ref Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/pins/pin\\_rivets/HST10AG8-8](https://military-fasteners.com/pins/pin_rivets/HST10AG8-8) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.