

Description

HST110AG8-8 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HST110AG88
Minimum Qty (MOQ):	5
NSN:	5320-01-513-6564
ECCN:	EAR99



* See page 2 for technical characteristics

P/N HST110AG8-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Head Style:	Err-090
Head Height:	0.059 Inches Minimum And 0.069 Inches Maximum
Width Between Flats:	0.094 Inches Minimum And 0.096 Inches Maximum
Shank Diameter:	0.264 Inches Minimum And 0.265 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.387 Inches Minimum And 0.412 Inches Maximum
End Item Identification:	CI-125, Aircraft
Grip Length:	0.820 Inches Minimum And 0.840 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	95000 Pounds Per Square Inch
Nominal Thread Size:	0.250 Inches
Shear Strength:	10490 Double Pounds Per Square Inch
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HST110AG8-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.