

**Description**

Diameter: 5/32", Grip Length: 1/8", flush shear head, titanium, aluminum coating

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[BACB30VU5K2](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | HST11AG52                                   |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5320-01-339-1501                            |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

## P/N HST11AG5-2 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Fastener Length:</b>                               | 0.395 Inches Minimum And 0.415 Inches Maximum  |
| <b>Head Style:</b>                                    | Flush Countersunk  |
| <b>Width Between Flats:</b>                           | 0.0635 Inches Minimum And 0.0645 Inches Maximum  |
| <b>Shank Diameter:</b>                                | 0.1625 Inches Minimum And 0.1635 Inches Maximum  |
| <b>Shank Style:</b>                                   | Pin-rivet, Straight, Threaded  |
| <b>Head Major Diameter:</b>                           | 0.2564 Inches Minimum And 0.2612 Inches Maximum  |
| <b>Lubrication:</b>                                   | Cetyl Alcohol, Spec 305, Hi-shear Corp   |
| <b>Grip Length:</b>                                   | 0.120 Inches Minimum And 0.130 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Nominal Thread Size:</b>                           | 0.164 Inches   |
| <b>Shear Strength:</b>                                | 95000 Single Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                             | 100.0 Degrees Nominal  |
| <b>Special Features:</b>                              | Color Code Orange On Thread End  |
| <b>Material:</b>                                      | Titanium Alloy Uns R56400 Overall  |
| <b>Material Document And Classification:</b>          | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Aluminum Overall   |
| <b>Surface Treatment Document And Classification:</b> | Hi Kote 1,cagec 73197 Mfr Ref Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unjc   |

## How to Order

Order this pin-rivet from our inventory online by visiting [https://military-fasteners.com/rivets/pin\\_rivets/HST11AG5-2](https://military-fasteners.com/rivets/pin_rivets/HST11AG5-2) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.