

Description

flush shear head, titanium, aluminum coating

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | HST11AG55 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-01-339-2102 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N HST11AG5-5 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.582 Inches Minimum And 0.602 Inches Maximum |
| Head Style: | Flush Countersunk |
| Width Between Flats: | 0.0635 Inches Minimum And 0.0645 Inches Maximum |
| Shank Diameter: | 0.1625 Inches Minimum And 0.1635 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.2564 Inches Minimum And 0.2612 Inches Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Grip Length: | 0.307 Inches Minimum And 0.317 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.164 Inches |
| Shear Strength: | 95000 Single Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Special Features: | Color Code Orange On Thread End |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall |
| Surface Treatment Document And Classification: | Hi Kote 1,cagec 73197 Mfr Ref Single Treatment Response Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HST11AG5-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.