

Description

flush shear head, titanium, aluminum coating

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HST11AG55
Minimum Qty (MOQ):	10
NSN:	5320-01-339-2102
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N HST11AG5-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.582 Inches Minimum And 0.602 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0635 Inches Minimum And 0.0645 Inches Maximum
Shank Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.2564 Inches Minimum And 0.2612 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Grip Length:	0.307 Inches Minimum And 0.317 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Color Code Orange On Thread End
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Hi Kote 1,cagec 73197 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/rivets/pin_rivets/HST11AG5-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.