

Description

HST12AG6-6 Pin-Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HST12AG66
Minimum Qty (MOQ):	10
NSN:	5320-01-513-5643
Schedule B:	8108.90.3060
ECCN:	EAR99

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HST12AG6-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Head Style:	Err-090
Head Height:	0.064 Inches Minimum And 0.074 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.080 Inches Maximum
Shank Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.357 Inches Minimum And 0.377 Inches Maximum
End Item Identification:	CI-125, Aircraft
Grip Length:	0.655 Inches Minimum And 0.675 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.191 Inches
Shear Strength:	5380 Double Pounds Per Square Inch
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/HST12AG6-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.