

## Description

Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	HST14816
Minimum Qty (MOQ):	25 EA
NSN:	5320-01-334-7979
Schedule B:	8803.30.0030
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N HST1481-6 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Identification Code Color:</b>	Green
<b>Collar Outside Diameter:</b>	0.345 Inches Minimum And 0.355 Inches Maximum
<b>Collar Overall Height:</b>	0.437 Inches Minimum And 0.457 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Collar Inside Diameter:</b>	0.208 Inches Minimum And 0.212 Inches Maximum
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Material:</b>	Aluminum Alloy 7075 Overall
<b>Material Document And Classification:</b>	Qq-a-225/9,t73 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Mil Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this hst collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HST1481-6](https://military-fasteners.com/collars/pin_rivet+collars/HST1481-6) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.