

Description

Thread Size: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HST7715
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-338-6922
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HST771-5 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.348 Inches Minimum And 0.352 Inches Maximum
Collar Overall Height:	0.375 Inches Minimum And 0.395 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.169 Inches Minimum And 0.173 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Collar Style:	Threaded (break Off) Type
Special Features:	Dye Color Green; Sealing Material Polytetrafluoroethylene
Heat Treatment:	T-73 Solution Heat Treated Overall
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-225/9 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this hst collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HST771-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.