

P/N HST79CY5

Description

HST79CY5 Pin-Rivet Collar

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information


SKU / Model: HST79CY5


Minimum Qty (MOQ): 10

NSN: 5320-01-338-6921

ECCN: EAR99

National Motor Freight: 096320, Rivets I / S Nickel Plated Buffed









^{*} See page 2 for technical characteristics

P/N HST79CY5 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.288 Inches Minimum And 0.292 Inches Maximum
Collar Overall Height:	0.375 Inches Minimum And 0.395 Inches Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.169 Inches Minimum And 0.173 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Collar Style:	Threaded (break Off) Type
Special Features:	Color Orange
Heat Treatment:	T-73 Solution Heat Treated Overall
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-225/9 Fed Spec Single Material Response Overall
Surface Treatment:	Oxide Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HST79CY5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.