

Description

HST79CY8 Pin-Rivet Collar

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | HST79CY8 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5320-01-340-0261 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



P/N HST79CY8 Specifications

| | |
|-------------------------------------------------------|-------------------------------------------------------|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Collar Outside Diameter: | 0.405 Inches Minimum And 0.412 Inches Maximum |
| Collar Overall Height: | 0.455 Inches Minimum And 0.476 Inches Maximum |
| Lubrication: | Cetyl Alcohol |
| Collar Inside Diameter: | 0.257 Inches Minimum And 0.261 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Nominal Thread Size: | 0.250 Inches |
| Collar Style: | Threaded (break Off) Type |
| Heat Treatment: | T-73 Solution Heat Treated Overall |
| Material: | Aluminum Alloy 7075 Overall |
| Material Document And Classification: | Qq-a-225/9 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this pin-riev collar from our inventory online by visiting https://military-fasteners.com/collars/pin_riev+collars/HST79CY8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.