P/N HST79CY8

Description

HST79CY8 Pin-Rivet Collar

* Manufacturer certifications are shipped with your order FREE of charge

[Order this part online]

Additional Information

SKU / Model:	HST79CY8
Minimum Qty (MOQ):	25
NSN:	5320-01-340-0261
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE AVAILABLE

* See page 2 for technical characteristics

P/N HST79CY8 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.405 Inches Minimum And 0.412 Inches Maximum
Collar Overall Height:	0.455 Inches Minimum And 0.476 Inches Maximum
Lubrication:	Cetyl Alcohol
Collar Inside Diameter:	0.257 Inches Minimum And 0.261 Inches Maximum
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Collar Style:	Threaded (break Off) Type
Heat Treatment:	T-73 Solution Heat Treated Overall
Material:	Aluminum Alloy 7075 Overall
Material Document And Classification:	Qq-a-225/9 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HST79CY8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.