

Description

Thread Size: 5-"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HSTM7005
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-366-4238
Schedule B:	7616.10.9090
ECCN:	9A991



\* See page 2 for technical characteristics

# P/N HSTM70-05 Specifications

Thread Direction:	Right-hand
Collar Outside Diameter:	7.90 Millimeters Minimum And 8.24 Millimeters Maximum
Collar Overall Height:	9.90 Millimeters Minimum And 10.42 Millimeters Maximum
Lubrication:	Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	5.62 Millimeters Minimum And 5.78 Millimeters Maximum
Nominal Thread Size:	5.0 Millimeters
Thread Pitch In Millimeters:	0.80
Collar Style:	Threaded (break Off) Type
Heat Treatment:	T-6 Solution Heat Treated Washer
Heat Treatment:	T-73 Solution Heat Treated Collar
Material:	Aluminum Alloy 2024 Washer
Material:	Aluminum Alloy 7075 Body
Material Document And Classification:	Qq-a-225/9 Fed Spec Single Material Response Collar
Material Document And Classification:	Qq-s-250/4 Fed Spec Single Material Response Washer Or Qq-a-250/5 Fed Spec Single Material Response Washer
Surface Treatment:	Anodize Collar
Thread Series Designator:	Iso M

## How to Order

Order this hst collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HSTM70-05](https://military-fasteners.com/collars/pin_rivet+collars/HSTM70-05) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.