

**Description**

Thread Size: 5-"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HSTM7005
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-366-4238
Schedule B:	7616.10.9090
ECCN:	9A991



## P/N HSTM70-05 Specifications

<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	7.90 Millimeters Minimum And 8.24 Millimeters Maximum
<b>Collar Overall Height:</b>	9.90 Millimeters Minimum And 10.42 Millimeters Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Collar Inside Diameter:</b>	5.62 Millimeters Minimum And 5.78 Millimeters Maximum
<b>Nominal Thread Size:</b>	5.0 Millimeters
<b>Thread Pitch In Millimeters:</b>	0.80
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Heat Treatment:</b>	T-6 Solution Heat Treated Washer
<b>Heat Treatment:</b>	T-73 Solution Heat Treated Collar
<b>Material:</b>	Aluminum Alloy 2024 Washer
<b>Material:</b>	Aluminum Alloy 7075 Body
<b>Material Document And Classification:</b>	Qq-a-225/9 Fed Spec Single Material Response Collar
<b>Material Document And Classification:</b>	Qq-s-250/4 Fed Spec Single Material Response Washer Or Qq-a-250/5 Fed Spec Single Material Response Washer
<b>Surface Treatment:</b>	Anodize Collar
<b>Thread Series Designator:</b>	Iso M

## How to Order

Order this hst collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HSTM70-05](https://military-fasteners.com/collars/pin_rivet+collars/HSTM70-05) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.