

Description

Thread Size: 5"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | HSTM7010 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5320-01-443-4706 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |



P/N HSTM70-10 Specifications

| | |
|-------------------------------------|--|
| Thread Direction: | Right-hand |
| Collar Outside Diameter: | 7.90 Millimeters Minimum And 8.24 Millimeters Maximum |
| Collar Overall Height: | 9.90 Millimeters Minimum And 10.42 Millimeters Maximum |
| Lubrication: | Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Collar Inside Diameter: | 5.62 Millimeters Minimum And 5.78 Millimeters Maximum |
| Nominal Thread Size: | 5.0 Millimeters |
| Thread Pitch In Millimeters: | 0.80 |
| Collar Style: | Threaded (break Off) Type |
| Heat Treatment: | T-6 Solution Heat Treated Washer |
| Heat Treatment: | T-73 Solution Heat Treated Collar |
| Material: | Aluminum Alloy 2024 Washer |
| Material: | Aluminum Alloy 7075 Body |
| Surface Treatment: | Anodize Collar |
| Thread Series Designator: | Iso M |

How to Order

Order this hst collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HSTM70-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.