

**Description**

Thread Size: 5"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HSTM7010
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-443-4706
Schedule B:	8108.90.3060
ECCN:	9A991



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

# P/N HSTM70-10 Specifications

<b>Thread Direction:</b>	Right-hand
<b>Collar Outside Diameter:</b>	7.90 Millimeters Minimum And 8.24 Millimeters Maximum
<b>Collar Overall Height:</b>	9.90 Millimeters Minimum And 10.42 Millimeters Maximum
<b>Lubrication:</b>	Cetyl Alcohol, Spec 305, Hi-shear Corp
<b>Collar Inside Diameter:</b>	5.62 Millimeters Minimum And 5.78 Millimeters Maximum
<b>Nominal Thread Size:</b>	5.0 Millimeters
<b>Thread Pitch In Millimeters:</b>	0.80
<b>Collar Style:</b>	Threaded (break Off) Type
<b>Heat Treatment:</b>	T-6 Solution Heat Treated Washer
<b>Heat Treatment:</b>	T-73 Solution Heat Treated Collar
<b>Material:</b>	Aluminum Alloy 2024 Washer
<b>Material:</b>	Aluminum Alloy 7075 Body
<b>Surface Treatment:</b>	Anodize Collar
<b>Thread Series Designator:</b>	Iso M

## How to Order

Order this hst collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/HSTM70-10](https://military-fasteners.com/collars/pin_rivet+collars/HSTM70-10) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.