

Description

Thread Size: 5-"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	HSTM94G05
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-465-5387
Schedule B:	8108.90.3060
ECCN:	9A991

A circular placeholder with a thin grey border containing the text "NO IMAGE AVAILABLE" in a sans-serif font.

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N HSTM94G05 Specifications

Thread Direction:	Right-hand
Collar Outside Diameter:	7.99 Millimeters Minimum And 8.24 Millimeters Maximum
Collar Overall Height:	9.90 Millimeters Minimum And 10.42 Millimeters Maximum
Lubrication:	Solid Film No. 905, Hi Shear Corp
Collar Inside Diameter:	5.62 Millimeters Minimum And 5.78 Millimeters Maximum
Nominal Thread Size:	5.0 Millimeters
Thread Pitch In Millimeters:	0.80
Thread Tolerance Class:	4h5h External
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 303se Overall
Material Document And Classification:	Astm A-582 Assn Std Single Material Response Overall
Thread Series Designator:	Iso M

How to Order

Order this hst collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/HSTM94G05 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.