



Military-Fasteners.com

P/N HT271A4-8

Description

Fastener Length: 63/64", Thread: 1/4-28, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | HT271A48 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-00-283-7455 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



* See page 2 for technical characteristics

P/N HT271A4-8 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.442 Inches Minimum And 0.509 Inches Maximum |
| Fastener Length: | 0.952 Inches Minimum And 0.999 Inches Maximum |
| Head Style: | Flat Countersunk Undercut |
| Head Diameter: | 0.502 Inches Minimum And 0.507 Inches Maximum |
| Head Height: | 0.071 Inches Minimum And 0.073 Inches Maximum |
| Grip Diameter: | 0.2490 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | High-torque |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 99.5 Degrees Minimum And 100.5 Degrees Maximum |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Special Features: | Furnished With One O-ring Seal |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Nas621 Comp 6al-4v Assn Std Single Material Response Overall Or Ams4928 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/HT271A4-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.