

Description

Fastener Length: 1-43/64", Thread: 7/16-20, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HT3097D19
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-013-9598
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N HT309-7D19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.466 Inches Nominal
Fastener Length:	1.638 Inches Minimum And 1.685 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.880 Inches Minimum And 0.890 Inches Maximum
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.111 Inches Maximum First Hole
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.438 Inches
Grip Length:	1.178 Inches Minimum And 1.198 Inches Maximum
Thread Quantity Per Inch:	20
Countersink Angle:	100.0 Degrees Nominal
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.510 Inches Minimum First Hole And 1.567 Inches Maximum First Hole
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Mac Ps13145,fscm 76301 Mfr Ref Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	76301-st3-562 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/HT309-7D19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.