

Description

Fastener Length: 21/32", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HT401644Y
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-045-2539
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE
AVAILABLE

P/N HT4016-4-4Y Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.372 Inches Minimum And 0.422 Inches Maximum
Fastener Length:	0.632 Inches Minimum And 0.662 Inches Maximum
Head Style:	Oval Countersunk
Head Diameter:	0.421 Inches Minimum And 0.426 Inches Maximum
Shoulder Diameter:	0.249 Inches Minimum First Shoulder And 0.2495 Inches Maximum First Shoulder
Shoulder Length:	0.176 Inches Minimum First Shoulder And 0.204 Inches Maximum First Shoulder
Internal Drive Style:	High-torque
End Item Identification:	Fms - Aircraft, Hornet F/a-18;aircraft, Eagle F-15;aircraft, Hornet F/a-18;aircraft, Harrier Av-8b
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Countersink Angle:	100.0 Degrees Nominal
Shoulder Shape:	Round First Shoulder
Special Features:	Socket Drive Recess In Thread End 0.095 Inch Nominal Width Across Flats
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/HT4016-4-4Y> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.