

**Description**

Fastener Length: 1-23/64", Thread: 7/16-20, Thread Length: 43/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | HT4028L711M                          |
| Minimum Qty (MOQ):      | 1 EA                                 |
| NSN:                    | 5305-01-050-4993                     |
| Schedule B:             | 8108.90.3060                         |
| ECCN:                   | EAR99                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE  
AVAILABLE

## P/N HT4028L7-11M Specifications

|                                     |  |
|-------------------------------------|--|
| <b>Thread Class:</b>                | 3a   |
| <b>Thread Direction:</b>            | Right-hand   |
| <b>Thread Length:</b>               | 0.631 Inches Minimum And 0.681 Inches Maximum              |
| <b>Fastener Length:</b>             | 1.329 Inches Minimum And 1.359 Inches Maximum              |
| <b>Head Style:</b>                  | Oval Countersunk   |
| <b>Head Diameter:</b>               | 0.662 Inches Minimum And 0.668 Inches Maximum              |
| <b>Grip Diameter:</b>               | 0.4365 Inches Minimum And 0.4370 Inches Maximum            |
| <b>Internal Drive Style:</b>        | High-torque  |
| <b>Nominal Thread Diameter:</b>     | 0.438 Inches   |
| <b>Grip Length:</b>                 | 0.678 Inches Minimum And 0.698 Inches Maximum              |
| <b>Thread Quantity Per Inch:</b>    | 20   |
| <b>Minimum Tensile Strength:</b>    | 160000 Pounds Per Square Inch                              |
| <b>Countersink Angle:</b>           | 100.0 Degrees Nominal                                      |
| <b>Surface Finish:</b>              | 32.0 Microinches Grip                                      |
| <b>Surface Finish:</b>              | 32.0 Microinches Threads                                   |
| <b>Surface Finish:</b>              | 32.0 Microinches Top Of Head                               |
| <b>Special Features:</b>            | Dry Film Lubricant P.s. 18021 Cl 1                         |
| <b>Material:</b>                    | Titanium Alloy Overall                                     |
| <b>Thread Series Designator:</b>    | Unjf   |
| <b>Specification/standard Data:</b> | 76301-st3-466 Professional/industrial Association Standard |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/HT4028L7-11M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.