

Description

Fastener Length: 9/16", Thread: 1/4-28, Thread Length: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HT4041445
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-131-2200
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N HT4041-4-4-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.287 Inches Minimum And 0.337 Inches Maximum
Fastener Length:	0.547 Inches Minimum And 0.577 Inches Maximum
Head Style:	Fillister Countersunk
Head Diameter:	0.390 Inches Minimum And 0.395 Inches Maximum
Head Height:	0.015 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	23-112,ty D,fscm 76301 Mfr Ref Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/HT4041-4-4-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.