

Description

Fastener Length: 55/64", Thread: 1/4-28, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | HT406746D |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-01-102-7955 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N HT4067-4-6D Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.335 Inches Minimum And 0.415 Inches Maximum |
| Fastener Length: | 0.829 Inches Minimum And 0.859 Inches Maximum |
| Head Style: | Flat Countersunk Undercut |
| Head Diameter: | 0.5018 Inches Minimum And 0.5066 Inches Maximum |
| Head Height: | 0.0713 Inches Minimum And 0.0733 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | High-torque |
| End Item Identification: | Aircraft,eagle F-15 |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.444 Inches Minimum And 0.494 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Steel Comp Xm-13 Overall |
| Material Document And Classification: | Ams 5629 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Mil-c-83488 Ty 2 Cl 3 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/HT4067-4-6D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.