

**Description**

Fastener Length: 1-19/64", Thread: 3/8-24, Thread Length: 41/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	HT4067612A
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-373-4839
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N HT4067-6-12A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.641 Inches Nominal
<b>Fastener Length:</b>	1.259 Inches Minimum And 1.306 Inches Maximum
<b>Head Style:</b>	Flat Countersunk Undercut
<b>Head Diameter:</b>	0.692 Inches Minimum And 0.763 Inches Maximum
<b>Head Height:</b>	0.1147 Inches Minimum And 0.1167 Inches Maximum
<b>Grip Diameter:</b>	0.3735 Inches Minimum And 0.3745 Inches Maximum
<b>Single Shear Strength:</b>	125000 Pounds Per Square Inch
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	0.624 Inches Minimum And 0.644 Inches Maximum
<b>Features Provided:</b>	Cetyl Alcohol Lubricant
<b>Thread Quantity Per Inch:</b>	24
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
<b>Material:</b>	Steel Comp Xm-13 Fastener
<b>Material Document And Classification:</b>	Ams 5629 Assn Std Single Material Response Fastener
<b>Surface Treatment:</b>	Aluminum Fastener And Chromate Fastener
<b>Surface Treatment Document And Classification:</b>	Mil-c-83488 Ty 2 Cl 3 Mil Spec Single Treatment Response Fastener
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/HT4067-6-12A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.