

Description

Fastener Length: 15/32", Thread: 10-32, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | HT406831A |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-102-9839 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N HT4068-3-1A Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.381 Inches Minimum And 0.431 Inches Maximum |
| Fastener Length: | 0.453 Inches Minimum And 0.483 Inches Maximum |
| Head Style: | Oval Countersunk |
| Head Diameter: | 0.2966 Inches Minimum And 0.3016 Inches Maximum |
| Grip Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| Internal Drive Style: | High-torque |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.052 Inches Minimum And 0.072 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 101.0 Degrees Nominal |
| Material: | Steel Comp Xm-13 Overall |
| Material Document And Classification: | Ams 5629 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Mil-c-83488 Ty 2 Cl 3 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/HT4068-3-1A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.