

Description

Fastener Length: 1-1/4", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	HT4069312A
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-530-6535
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N HT4069-3-12A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.406 Inches Nominal
Fastener Length:	1.275 Inches Nominal
Head Style:	Oval Countersunk
Head Diameter:	0.297 Inches Minimum And 0.302 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 1.189 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	100.0 Degrees Nominal
Part Name Assigned By Controlling Agency:	Screw-close Tolerance
Material:	Nickel Alloy 718 Overall
Material Document And Classification:	Ams 5662 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall And Chromate Overall
Surface Treatment Document And Classification:	Mil-c-83488 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/HT4069-3-12A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.