

**Description**

Fastener Length: 13/16", Thread: 10-32, Thread Length: 21/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | HT4072385                                 |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5305-01-097-7917                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N HT4072-3-8-5 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.287 Inches Minimum And 0.337 Inches Maximum                         |
| <b>Fastener Length:</b>                               | 0.797 Inches Minimum And 0.827 Inches Maximum                         |
| <b>Head Style:</b>                                    | Oval Countersunk  |
| <b>Head Diameter:</b>                                 | 0.2966 Inches Minimum And 0.3016 Inches Maximum                       |
| <b>Grip Diameter:</b>                                 | 0.1885 Inches Minimum And 0.1895 Inches Maximum                       |
| <b>Internal Drive Style:</b>                          | High-torque   |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Grip Length:</b>                                   | 0.490 Inches Minimum And 0.510 Inches Maximum                         |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Countersink Angle:</b>                             | 100.0 Degrees Nominal   |
| <b>Material:</b>                                      | Steel Corrosion Resisting Overall                                     |
| <b>Material Document And Classification:</b>          | 23-112 Fscm 73197 Mfr Ref Single Material Response Overall            |
| <b>Surface Treatment:</b>                             | Aluminum Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-c-83488,type 2,class 3 Mil Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjf  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/HT4072-3-8-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.