

Description

Thread Size: 1/8", Head Width: 1/4

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	KFN54208
Minimum Qty (MOQ):	25
NSN:	5310-01-119-6793
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N KFN542-08 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Washer Outside Diameter:	0.340 Inches Maximum
Counterbore Diameter:	0.197 Inches Minimum Nut And 0.202 Inches Maximum Nut
Overall Height:	0.240 Inches Maximum
Nut Style:	Flat With Turned Up Edge
Nut Counterbore Depth:	0.087 Inches Minimum Nut And 0.097 Inches Maximum Nut
Width Across Flats:	0.212 Inches Minimum And 0.220 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Hardness Rating:	39.0 Rockwell C Minimum And 43.0 Rockwell C Maximum
Nominal Thread Size:	0.164 Inches
Special Features:	Washer Rockwell C Scale 40.0 Min And Rockwell C Scale 45.0 Max
Material:	Steel Comp 8740 Overall Or Steel Comp 4340 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2 Cl2 Mil Spec Single Treatment Response Overall

How to Order

Order this self-locking assembled washer nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+assembled+washer+nuts/KFN542-08 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.